



GuardALL[®]
Guard for ALL

PRODUCT
CATALOG

GuardALL

DRY POWDER

Dry Powder is highly versatile. Class A, B & C fire fighting medium suitable for most risk. In addition to dealing with electrical hazards, flammable liquids and gases, powder also effective for vehicle fires.



FIRE EXTINGUISHER



Wood, Paper,
Textile, Fabric



Petrol, Diesel,
Oils



Electrical



Magnesium, Titanium,
Potassium

TYPE	GAP-1	GAP-2	GAP-3	GAP-5	GAP-6	GAP-9
Height (cm)	31	42	46	51	51	63
Width (cm)	11	19	19	22	22	25
Diameter (cm)	8.9	11.1	12.7	14.6	14.6	17
Capacity (kg)	1	2	3	5	5	9
Weight full (kg)	1.6 ^o	3.3	4.4	6.7	6.7	13
Weight empty (kg)	0.6	1.3	1.4	1.7	1.7	4
Discharge time (sec)	8	13	14	15	15	21
Discharge range (m)	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12
Test pressure (bar)	25	25	25	25	25	25
Working pressure at 20°C	15	15	15	15	15	15
Minimum effective discharge (%)	90	90	90	90	90	90
Temperature range (0°C)	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60
Fire rating	8A : 34B	21A : 70B	21A : 89B	29A : 165B	29A : 165B	43A : 233B

FOAM

Spray foam extinguishers are suitable for both A & B fire. Spray Foam has the ability to reduce the risk of reignition once the fire has been extinguished the foam effectively seals the vapours at the same time as cooling the fire.



Wood, Paper,
Textile, Fabric



Petrol, Diesel,
Oils

TYPE	GFO-6	GFO-9
Height (cm)	55	63
Width (cm)	25	25
Diameter (cm)	16.5	17
Capacity (kg)	6	9
Weight full (kg)	9.6	13.6
Weight empty (kg)	3	4
Discharge time (sec)	27	29
Discharge range (m)	3 to 12	3 to 12
Test pressure (bar)	25	25
Working pressure at 20°C	15	15
Minimum effective discharge (%)	90	90
Temperature range (0°C)	0 to 60	0 to 60
Fire rating	13A : 144B	21A : 183B

CO₂

CO₂ is suitable for electrical equipment, Class B fires and recognized for its non-damaging highly effective performance and cleanliness. GuardALL CO₂ have non-conductive anti-static horns. A protection to withstand extreme temperatures, dirty environment and UV degradation.



Petrol, Diesel,
Oil



Electrical

TYPE	GCO-2,2	GCO-3	GCO-5	GCO-6,8
Height (cm)	49	66	69	84
Width (cm)	18	18	25	33
Diameter (cm)	11	11	15	15
Capacity (kg)	2,2	3	5	6,8
Weight full (kg)	7.9	10,6	15,4	25,3
Weight empty (kg)	5,7	7,6	10,4	18,5
Discharge time (sec)	8	10	18	23
Discharge range (m)	3 to 12	3 to 12	3 to 12	3 to 12
Test pressure (bar)	200	200	200	200
Working pressure at 20°C	56	56	56	56
Minimum effective discharge (%)	90	90	90	90
Temperature range (0°C)	-20 to 60	-20 to 60	-20 to 60	-20 to 60
Fire rating	34B	36B	34B	77B